


Prosport Inc. Premium Boost Gauge

Amber/White Display (270° Scale)

1. Wiring Back of Gauge

(Daisy Chain power wire to next gauge plugs in here.)



2. Setting warning / Mute Feature

To set the warning feature:

After the opening ceremony is complete, Press and hold the button down for approx 5 seconds until the pointer begins to blink. Release button. Push and hold button to move quickly across the scale or Toggle button to move pointer in small increments. Once you have the pointer where you want it, wait 5 seconds to "set" and pointer will stop blinking

Mute feature:


- 1.) With ignition key in off position, press and hold button- Turn Ignition on, wait for pointer to come to a rest then release button.
- 2.) To turn sound back on-Repeat step 1

Peak recall

- 1.) Push button one time to recall peak level. The Blue light will come on when gauge is in recall mode. The pointer will rise to the Highest level attained by the gauge and remain there approximately 5 seconds.
- 2.) To reset peak level: While in peak mode (blue light is on) press and hold button down

3. Installing Boost sender

Cut boost line and install supplied plastic "T" fitting. Connect "T" fitting to In-Line Filter with supplied hose. Then connect In-Line Filter to sender with supplied hose.



Lighting Diagram

Day Time	Night Time	Installation
White	White	White — Connect to acc. Power Amber — Do not connect
Amber	Amber	White — Do not connect Amber — Connect to acc. Power
White	Amber	White — Connect to acc. Power Amber — Connect to parking lamp
Amber	White	Amber — Connect to acc. Power White — Connect to parking lamp

